

Description

The MGLEVP is a slim recessed LED panel with an opal diffuser suitable for offices and education

Environment

Indoor

Installation

Fits 15-24mm T-bar ceiling 600x600mm

Application

For use retail, education and commercial applications.



5YR

Warranty

IP40

Protection

50,000hrs

Lifetime

IK02

Toughness

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.90
Light Source	LED
LED Lifetime	50,000hrs/ L70B50
Operating temperature	0°C to 35°C
Materials	Aluminium body - white finish Opal edge lit diffuser

Light Data

Lumens per Watt	97-102lm/W
-Light Source	LED
CRI	80
Light Distribution	Direct

Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Length mm	Width mm	Height mm	Weight kg
MGLEVP LED1X3600 D550 T830 OP	36	97	3480	3000	595	595	11	3.2
MGLEVP LED1X3600 D539 T830 OP	36	97	3480	3000	1195	295	11	3.4
MGLEVP LED1X3600 D550 T840 OP	36	102	3680	4000	595	595	11	3.2
MGLEVP LED1X3600 D539 T840 OP	36	102	3680	4000	1195	295	11	3.4
MGLEVP LED1X3650 G090 T830 OP	36	100	3600	3000	595	595	33	1.8
MGLEVP LED1X3650 G091 T830 OP	36	100	3600	3000	1195	295	33	1.8
MGLEVP LED1X3650 G090 T840 OP	36	101	3650	4000	595	595	33	1.8
MGLEVP LED1X3650 G091 T840 OP	36	101	3650	4000	1195	295	33	1.8

Options

OPTION	CODE
Driver with DALI interface	DALI
Driver with DALI interface, switch control dimming and double input terminals for looping the main cables.	DALI LOOP
Emergency version 3 hours	EM3
Emergency version 3 hours with DALI interface	EM3D

Accessories

ACCESSORY	CODE
Recessed frame 595x595 for installation into plasterboard ceiling (1pc) White	MTGFS620
Surface mounting box for LED panel 595x595 (1pc) White	MTGBOX
Decorative cover with 500mm round opening for LED panel 595x595 (1pc) White	DECOV



Decorative cover