

# Helix 2

## V418301 - V418310

### Description

The Helix 2 is a range of bulkheads with triac dimming as standard.

### Environment

Indoor

### Installation

Designed to be ceiling or wall mounted

### Application

For use apartment blocks, care homes, corridors, hotels, schools and similar applications



### General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	3000K/4000K
LED Lifetime	40,000hrs
Operating temp	-15°C to 35°C
Materials	Polycarbonate base and diffuser.

### Light Data

Lumens per Watt	95-100lm/W
Light Source	LED
CRI	80
Distribution	110°

# Helix 2

## V418301 - V418310

### Product Variants

Product Code	Description	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Diameter mm	Height mm
V418301	Triac Dimmable	12W	95	1180	3000	200	48
V418302	Triac Dimmable	12W	100	1245	4000	200	48
V418303	Triac Dimmable	18W	95	1770	3000	300	40
V418304	Triac Dimmable	18W	100	1800	4000	300	40
V418305	Adjustable sensor with CF (option)	20W	95	1950	3000	300	40
V418306	Adjustable sensor with CF (option)	20W	100	2050	4000	300	40
V418307	Triac Dimmable	25W	95	2450	3000	300	40
V418308	Triac Dimmable	25W	100	2570	4000	300	40
V418309	Triac Dimmable	30W	95	2850	3000	400	52
V418310	Triac Dimmable	30W	100	3000	4000	400	52

### Options

OPTION	CODE
3 Hour Emergency	/M3
Inbuilt Microwave Sensor	/MS

### Accessories

OPTION	CODE
Chrome ring for V418303/304 /307 and 308 models	AV418301
Chrome ring for emergency versions of V418303/304/ 307 and 308	AV418301/M3

