

NGN6 Downlight

V48901- V48909

Description

A range of IP65 recessed downlights with COB LED lightsource.

Environment

Indoor

Installation

Designed to be recessed mounted

Application

For use in retail or commercial applications.



5YR

Warranty

IP65

Protection

50,000hrs

Lifetime

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	3000K, 4000K or 6000K
LED Lifetime	50,000hrs
Operating temp	0°C to 35°C
Materials	Diecast housing

Light Data

Lumens per Watt	90-105lm/W
Light Source	LED
CRI	80
Distribution	Direct

MGN6 Downlight

V48901- V48909

Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Cut out (mm)	Dimensions (mm)
V48901	5	90	650	3000	93	103X50
V48902	5	100	700	4000	93	103X50
V48903	5	100	700	6000	93	103X50
V48904	15	100	1550	3000	152	170X60
V48905	15	1105	1635	4000	152	170X60
V48906	15	105	1635	6000	152	170X60
V48907	28	100	2800	3000	215	224X85
V48908	28	105	2900	4000	215	224X85
V48909	28	105	2900	6000	215	224X85

Options

OPTION	CODE
1-10V Dimming	/D
DALI and switch Dimming	/DD
DSI Digital Dimmable	/DL
Trailing Edge Dimming	/TD
3 Hour Emergency	/M3
Self Test 3 Hour Emergency	/ST

Satin Chrome Ring

Black Ring

White Ring

Extension Ring with fitting installed

MG Lites, 4 Denaby Lane Industrial Estate, Coalpit Road, Denaby, Doncaster, South Yorkshire, DN12 4LH