

AquaLED 6

V414501 - V414516

Description

The AquaLED 6 is a range of IP65 anti-corrosive fittings ideal for use in warehouses, retail and commercial applications.

Environment

Outdoor/Indoor

Installation

Designed to be suspended or ceiling mounted

Application

For use in commercial applications.



General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	5000K or 3CCT
LED Lifetime	50,000hrs
Operating temp	-20°C to 30°C
Materials	Polycarbonate body and cover. Supplied with stainless steel clips

Light Data

Lumens per Watt	90-145lm/W
Light Source	LEDs
CRI	80
Distribution	120°

AquaLED 6

V414501 - V414516

Product Variants

Product Code	System Power (W)	System Efficacy (lm/W)	Lumens (lm)	CCT (K)	Length mm	Width mm	Height mm
V414501	20	95	1900	5000K	600	600	73
V414502	20	90	1810-1900	3CCT	600	600	73
V414503	21	100	2110	5000	1200	100	73
V414504	21	90	1950-2110	3CCT	1200	100	73
V414505	41	95	3990	5000	1200	100	73
V414506	41	90	3700-3990	3CCT	1200	100	73
V414507	29	95	2800	4000	1500	100	73
V414508	29	100	2900	5000	1500	100	73
V414509	57	90	5300	4000	1500	100	73
V414510	57	90	5300	5000	1500	100	73
V414511	57	90	5150-5300	3CCT	1500	100	73
V414512	67	125	8500	4000	1500	100	73
V414513	67	130	8980	5000	1500	100	73
V414514 (clear diffuser)	27	145	3710	4000	1500	100	73
V414515 (clear diffuser)	45	140	6500	4000	1500	100	73
V414516 (prewired with 3m flex)	45	140	6500	4000	1500	100	73

Options

OPTION	CODE
1-10V Dimming	/D
DALI Dimming	/DL
DSI Digital Dimming	/DD
Trailing Edge Dimming	/TD
3 Hour Emergency	/M3
3 Hour Emergency Self Test	/ST
Batten Mounted PIR	/PIR
Inbuilt Microwave Sensor	/MS

MG Lites, 4 Denaby Lane Industrial Estate, Coalpit Road, Denaby, Doncaster, South Yorkshire, DN12 4LH