

MGSL Street Light

V415901 -v415904

Description

The MGSL is a high performance slimline street light ideal for residential areas and roadways.

Environment

Outdoor

Installation

Designed to be pole or wall mounted

Application

For use in car parks, walkways, housing estates and roadways.



General Data

| | |
|----------------|--|
| Voltage | AC220-240V 50-60Hz |
| Power Factor | >0.9 |
| Light Source | LED |
| CCT | 3500K as standard |
| LED Lifetime | 114000hrs/L80B20 @ Ta25 degrees |
| Operating temp | -30°C to 50°C |
| Materials | Aluminium alloy body Polycarbonate lens |

Light Data

| | |
|-----------------|--------|
| Lumens per Watt | 115lm/ |
| Light Source | LED |
| CRI | 80 |
| Distribution | Direct |

MGSL Street Light

V415901-V415904

Product Variants

| Product Code | System Power (W) | Lumens (lm) | CCT (K) | Length (mm) | Width (mm) | Height (mm) |
|--------------|------------------|-------------|---------|-------------|------------|-------------|
| V415901 | 30W | 3600 | 3500K | 478 | 166 | 141 |
| V415902 | 50W | 5800 | 3500K | 478 | 166 | 141 |
| V415903 | 90W | 12150 | 3500K | 507 | 203 | 87 |
| V415904 | 150W | 19500 | 3500K | 507 | 203 | 87 |

Options


| OPTION | CODE |
|---------------------|------|
| DSI Digital Dimming | /DD |
| DALI dimming | /DL |
| Photocell | /PC |

Accessories

| ACCESSORY | CODE |
|-------------------------------------|----------|
| Photocell blanking cap | AV415901 |
| 10amp photocell nema head | AV415902 |
| 60mm flat wall mounting bracket | AV415903 |
| 60mm twin T shape mounting bracket | AV415904 |
| 60mm corner wall mounting bracket | AV415905 |
| 60mm L shape pole extension bracket | AV415906 |



AV415905



AV415903



AV415906



AV415904