

Description

The MGCAPA is a cylindrical LED track light with symmetrical faceted reflector designed for accent lighting.

Environment

Indoor

Installation

Designed to be surface mounted

Application

Suitable for retail, showrooms, museums, exhibition stands and other similar applications



General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.95
Light Source	LED
LED Lifetime	50,000hrs/ L80B50
Operating temperature	0°C to +35°C
Materials	Clear PMMA diffuser Faceted aluminium reflector 40 degree standard Aluminium white finish body with adaptor
Installation	Designed to be fixed into 4/6 conductor surface/recessed tracks. Track adaptor (3phase + N) with phase selector

Light Data

Lumens per Watt	99-117lm/W
Light Source	LED
CRI	80
Distribution	Direct


Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Length mm	Width mm	Height mm	Weight kg
MGCAPA LED1X1650 E842 T830 R40	13.8	117	1604	3000	206	82	154	1.3
MGCAPA LED1X2300 E843 T830 R40	19.1	116	2226	3000	206	82	154	1.3
MGCAPA LED1X3100 E844 T830 R40	27.5	109	3002	3000	206	82	154	1.3
MGCAPA LED1X3950 E845 T830 R40	34.4	111	3830	3000	195	99	198	1.5
MGCAPA LED1X1650 E842 T840 R40	13.8	119	1644	4000	206	82	154	1.3
MGCAPA LED1X2300 E843 T840 R40	19.1	119	2282	4000	206	82	154	1.3
MGCAPA LED1X3100 E844 T840 R40	27.5	112	3079	4000	206	82	154	1.3
MGCAPA LED1X3950 E845 T840 R40	34.4	114	3930	4000	195	99	198	1.5
MGCAPA LED1X1650 E842 T930 R40	13.3	99	1312	3000	206	82	154	1.3
MGCAPA LED1X2300 E843 T930 R40	18.4	100	1839	3000	206	82	154	1.3
MGCAPA LED1X3100 E844 T930 R40	26.3	96	2511	3000	206	82	154	1.3
MGCAPA LED1X3950 E845 T930 R40	34.5	91	3154	3000	195	99	198	1.5
MGCAPA LED1X1650 E842 T940 R40	13.3	106	1403	4000	206	82	154	1.3
MGCAPA LED1X2300 E843 T940 R40	18.4	107	1965	4000	206	82	154	1.3
MGCAPA LED1X3100 E844 T940 R40	26.3	102	2684	4000	206	82	154	1.3
MGCAPA LED1X3950 E845 T940 R40	34.5	98	3370	4000	195	99	198	1.5




Options


Reflector with 24 degree light beam angle	R24
Reflector with 40 degree light beam angle	R40
Reflector with 60 degree light beam angle	R60
CCT 3000K CRI 80+	T830
CCT 4000K CRI 80+	T840
CCT 3000K CRI 90+	T930
CCT 4000K CRI 90+	T930
CCT 2700K CRI97+	T924
CCT light pink CRI 65+	T6LP
Special spectrum for meat	MEAT
Special spectrum for bread	BREAD
Black body and adaptor	RAL9005



R24



R40



R60