

Corona 3

V417501- V417508

Description

The Corona 3 is a range of ceiling or wall mounted bulkheads.

Environment

Indoor

Installation

Designed to be ceiling or wall mounted

Application

For use apartment blocks, care homes, corridors, hotels, schools and similar applications



General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	4000K / 3CCT
LED Lifetime	54,000/L80B10
Operating temp	-15°C to 35°C
Materials	Polycarbonate housing and diffuser. BESA box knockouts on base

Light Data

Lumens per Watt	110-125lm/W
Light Source	LED
CRI	80
Distribution	110°

Corona 3

V417501- V417508

Product Variants

Product Code	Description	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Diameter mm	Height mm
V417501	Clear base for halo effect	18W	125	2250	4000K	435	110
V417502	Clear base for halo effect	18W	125	2250	3CCT	435	110
V417503	White base	18W	110	2030	4000K	435	110
V417504	White base	18W	110	2030	3CCT	435	110
V417505	Clear base for halo effect	30W	125	3910	4000K	470	110
V417506	Clear base for halo effect	30W	125	3910	3CCT	470	110
V417507	White base	30W	110	3480	4000K	470	110
V417508	White base	30W	110	3480	3CCT	470	110

Options

OPTION	CODE
1-10V Dimming	/D
DALI Dimming	/DL
DSI Digital Dimming	/DD
Leading/Trailing Edge Dimming	/TD
3 Hour Emergency	/M3
Self Test 3 Hour Emergency	/ST
Inbuilt Corridor Function	/CF
Inbuilt Microwave Sensor	/MS
Night Light	/NL

Accessories

OPTION	CODE
Polished chrome ring for V417501 - V417504	AV417501
Satin chrome ring for V417501 - V417504	AV417502
Polished chrome ring for V417505 - V417508	AV417503
Satin chrome ring for V417505 - V417508	AV417504



V417505