

## Description

The Corona 4 is a highly efficient and decorative bulkhead.

## Environment

Indoor

## Installation

Designed to be wall or ceiling mounted

## Application

Suitable hotels, schools, care homes and other similar applications



**5YR**

Warranty



**IP44**

Protection

**50,000hrs**

Lifetime

## General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.90
Light Source	LED
LED Lifetime	50,000hrs/ L80B50
Operating temperature	0°C to +35°C
Materials	Sheet metal housing with glass diffuser
Installation	Designed to be wall or ceiling mounted.

## Light Data

Lumens per Watt	>85lm/W
Light Source	LED
CRI	80
Distribution	Direct

## Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Dimensions Diameter x height mm
V417701	12W	>85	1100	3000	410x90
V417702	12W	>85	1120	4000	410x90
V417703	12W	>85	1150	6000	410x90
V417704	20W	>85	1700	3000	410x90
V417705	20W	>85	1720	4000	390x100
V417706	20W	>85	1750	6000	390x100
V417707	30W	>85	2550	3000	420x100
V417708	30W	>85	2580	4000	420x100
V417709	30W	>85	2600	6000	420x100

## Options

DALI and switch dimmable	DL
1-10V Dimming	D
DSI Digital dimmable	DD
Leading/ tailing edge dimmable	TD
Inbuilt microwave sensor	MS
Corridor Function	CF

