

Description

The MGLEO is a surface IP54 LED luminaire with opal diffuser and decorative indirect wall light effect.

Environment

Outdoor

Installation

Designed to be surface mounted

Application

Suitable for parking areas, public areas and other similar applications



5YR Warranty	 IP54 Protection	50,000hrs Lifetime	 IK08 Toughness
------------------------	--	------------------------------	---

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.80
Light Source	1XE27/LED
LED Lifetime	50,000hrs/ L80B50
Operating temperature	-25°C to +40°C
Materials	Opal polycarbonate diffuser, impact resistant Die-cast aluminium body, dark grey finish
Installation	Designed to surface mounted

Light Data

Lumens per Watt	50-86lm/W
Light Source	LED
CRI	80
Distribution	Direct/indirect


Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Length mm	Width mm	Height mm	Weight kg
MGLEO 1E27 C402					265	265	90	1.6
MGLEO LED1X1200 D034 T830	13.6	82	1118	3000	265	265	90	1.7
MGLEO LED1X1200 D034 T840	13.6	86	1173	4000	265	265	90	1.7
MGLEO 1E27 C402 LOUVRE					265	265	100	1.9
MGLEO LED1X1200 D034 T830 LOUVRE	13.6	50	688	3000	265	265	100	2
MGLEO LED1X1200 D034 T840 LOUVRE	13.6	53	722	4000	265	265	100	2


Options

Decorative louvre	LOUVRE
Driver with DALI interface	DALI
Microwave Sensor	MW
CCT 3000K CRI 80+	T830
CCT 4000K CRI 80+	T840

Photometrics



STANDARD



LOUVRE