

MGC Flood Light

V415101 - V415112

Description

The MGC Flood light is a range of IP66 rated, efficient and durable luminaires.

Environment

Outdoor

Installation

Designed to be wall or pole mounted

Application


For large open areas, car parks, garages, walkways and other similar applications.




5YR Warranty	 IP66 Protection	50,000hrs Lifetime
------------------------	---	------------------------------

General Data


Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	4000K or 6000K
LED Lifetime	50,000hrs
Operating temp	-30°C to 50°C
Materials	Aluminium alloy body in black, tempered glass diffuser



Type 1



Type 2



Type 3

Light Data

Lumens per Watt	125-135lm/W
Light Source	LED
CRI	80
Distribution	15°, 30°, 60°, 90° and Asymmetric Type 1, 2 or 3 options

MGC Flood Light

V415101 - V415112

Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Length (mm)	Width (mm)	Height (mm)
V415101	30W	135	4050	4000	300	240	69
V415102	30W	135	4050	6000	300	240	69
V415103	50W	125	6250	4000	300	240	69
V415104	50W	125	6250	6000	300	240	69
V415105	100W	125	12500	4000	335	295	71
V415106	100W	125	12500	6000	335	295	71
V415107	150W	125	18750	4000	375	320	75
V415108	150W	125	18750	6000	375	320	75
V415109	200W	125	25000	4000	400	345	78
V415110	200W	125	25000	6000	400	345	78
V415111	300W	125	37500	4000	464	410	83
V415112	300W	125	37500	6000	464	410	83

Options

OPTION	CODE
Beam angle 15, 30, 60, 90 degree, Type 1, 2,3	/15, /30, /60, /90, /T1, /T2, /T3
DALI & Switch Dimmable	/DL
DSI Digital Dimmable	/DD

Accessories

OPTION	CODE
Pole mounting adaptor for 42mm pole	AV415101
Pole mounting adaptor for 60mm pole	AV415102
Pole mounting adaptor for 76mm pole	AV415103
Pole mounting clamp	AV415104

