

Slimline Bulkhead

V418701 - V418706

Description

The Slimline bulkhead is a range of low profile bulkheads in a range of options.

Environment

Outdoor/Indoor

Installation

Designed to be wall mounted

Application

For use schools, stairwells and other similar applications



General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	4000K
LED Lifetime	30,000hrs
Operating temp	-15°C to 35°C
Materials	Polycarbonate base and diffuser.

Light Data

Lumens per Watt	70lm/W
Light Source	LED
CRI	80
Distribution	110°

Slimline Bulkhead

V418701 - V418706

Product Variants

Product Code	Description	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Length mm	Width mm	Height mm
V418701	Rectangular, black and white trim	15W	70	1100	4000	212	45	120
V418702	Rectangular, black trim inbuilt PIR	15W	70	1100	4000	212	45	120
V418703	Rectangular, white trim inbuilt PIR	15W	70	1100	4000	212	45	120

Product Code	Description	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Diameter mm	Height mm
V418704	Circular, black and white trim	15W	70	1100	4000	210	49
V418705	Circular black trim inbuilt PIR	15W	70	1100	4000	210	49
V418706	Circular white trim inbuilt PIR	15W	70	1100	4000	210	49



V418705



V418704



V418701



V418703