

## Description

The MGTHEA is a recessed IP54 wall mounted LED luminaire suitable for parking areas, tunnels and façade lighting.

## Environment

Outdoor

## Installation

Designed to be wall mounted

## Application

Suitable for parking areas, tunnels, public areas and other similar applications



## General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.50
Light Source	1XE27/LED
LED Lifetime	50,000hrs/ L80B50
Operating temperature	-25°C to +40°C
Materials	Frosted tempered glass diffuser, impact resistant Die-cast aluminium body, dark grey finish
Installation	Designed to recessed mounted

## Light Data

Lumens per Watt	31-64lm/W
Light Source	LED
CRI	80
Distribution	Direct

## Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Length mm	Width mm	Height mm	Weight kg
MGTHEA 1E27 Q75					255	90	70	1
MGTHEA LED1X300 D058 T830	3.6	62	222	3000	255	80	70	1.2
MGTHEA LED1X300 D058 T840	3.6	64	232	4000	255	80	70	1.2
MGTHEA 1W27 Q75 GRID					255	90	70	1
MGTHEA LED1X300 D058 T830 GRID	3.6	31	111	3000	255	80	70	1.2
MGTHEA LED1X300 D058 T840 GRID	3.6	32	116	4000	255	80	70	1.2

## Options

Protective grid	GRID
CCT 3000K CRI 80+	T830
CCT 4000K CRI 80+	T840

## Photometrics

