

Corona 5

V417901- V417909

Description

The Corona 5 is a range of efficient and decorative ceiling or wall mounted bulkheads.

Environment

Indoor

Installation

Designed to be ceiling or wall mounted

Application

For use apartment blocks, car homes, corridors, hotels schools and stairwells



General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	4000K
LED Lifetime	50,000hrs
Operating temp	0°C to 35°C
Materials	PMMA opal diffuser

Light Data

Lumens per Watt	85lm/W
Light Source	LED
CRI	80
Distribution	110°

Corona 5

V417901- V417909

Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Diameter mm	Height mm
V417901	12	85	1100	3000K	340	100
V417902	12	85	1120	4000K	340	100
V417903	12	85	1150	6000K	340	100
V417904	20	85	1700	3000K	340	100
V417905	20	85	1720	4000K	340	100
V417906	20	85	1750	6000K	340	100
V417907	30	85	2550	3000K	400	100
V417908	30	85	2580	4000K	400	100
V417909	30	85	2600	6000K	400	100

Options

OPTION	CODE
1-10V Dimming	/D
DALI Dimming	/DL
DSI Digital Dimming	/DD
Leading/Trailing Edge Dimming	/TD
3 Hour Emergency	/M3
Self Test 3 Hour Emergency	/ST
Inbuilt Corridor Function	/CF
Inbuilt Microwave Sensor	/MS