

MN2 Panel

V47501 - V47507

Description

The MN2 is an LED panel with direct/indirect light diffusion ideal for use in schools, open plan offices, call centres and similar applications.

Environment

Indoor

Installation

Designed to be fitted in standard 15mm or 24mm ceiling grid



Application

For use in commercial applications.

5YR Warranty	 IP20 Protection	50,000hrs Lifetime
------------------------	---	------------------------------

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	4000K
LED Lifetime	50,000hrs
Operating temp	-15°C to 25°C
Materials	Steel body white finish, Centre grid louvre or opal cover and indirect side shade
Installation	To fit in standard 15mm or 24mm ceiling grid

Light Data

Lumens per Watt	85-90lm/W
Light Source	LEDs
CRI	80
Distribution	Direct/indirect

MN2 Panel V47501 - V47507

Product Variants

Product Code	Description	System Power (W)	Lumen s (lm)	CCT (K)	Length mm	Width mm	Height mm
V47501	Aluminium grid	20W	1740	4000	595	595	110
V47502	Aluminium grid	40W	3500	4000	595	595	110
V47503	Opal PMMA	20W	1950	4000	595	595	110
V47504	Opal PMMA	40W	3900	4000	595	595	110
V47505	Micro prismatic	20W	1850	4000	595	595	110
V47506	Micro prismatic	40W	3700	4000	595	595	110
V47507	Aluminium grid	20W	3600	4000	595	595	110

Options

OPTION	CODE
1-10V Dimming	/D
DALI Dimming	/DL
DSI Digital Dimming	/DD
Trailing Edge Dimming	/TD
3 Hour Emergency	/M3
3 Hour Emergency Self Test	/ST
Inbuilt PIR Sensor	/PIR
CCT 3000K or 6000K	/3K or /6K



Centre Louvred version

Accessories

ACCESSORY	CODE
Plasterboard clips for recessing into plasterboard ceiling (4pcs)	MGC/CLIPS