

MGC Stadium Flood V415501

Description

The MGC stadium flood is a high powered flood light with an asymmetrical beam angle suitable for large areas like football pitches and stadiums.

Environment

Outdoor

Installation

Designed to be pole mounted

Application

Suitable for sports pitches, stadiums, tennis courts and other similar applications.



5YR

Warranty

IP66

Protection

50,000hrs

Lifetime

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
CCT	5000K as standard
Driver	Inventronics
LED Lifetime	50,000
Operating temperature	-30°C to 50°C
Gearbox	Remote gearbox for easy wiring
Surge Protection	10Kv
Materials	Diecast aluminium body Tempered glass diffuser

Light Data

Lumens per Watt	135lm/W
Light Source	LED
CRI	80

MGC Stadium Flood V415501

Product Variants

Product Code	System Power (W)	Lumens (lm)	Length (mm)	Width (mm)	Height (mm)
V415501	565	79,640	406	404	432

Options

OPTION	CODE
DALI Dimming	/DL
1-10V Dimming	/D
DSI Digital dimmable	/DD
10 degree lens	AV415502
15 degree lens	AV415503
30 degree lens	AV415504
CCT Options 4000k or 6000K	/4K or /6K
Visor for Flood	AV415501



Remote gearbox



Side profile



Back profile