

MGCLD Downlight

V410001- V410006

Description

A range of stylish downlights with a microprism diffuser to reduce glare.

Environment

Indoor

Installation

Designed to be recessed mounted

Application

For use in retail, offices, showrooms and other similar applications.



3/5YR

Warranty

IP44


Protection

40,000hrs

Lifetime

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	3000K/4000K
LED Lifetime	40,000hrs
Operating temp	-15°C to 25°C
Materials	Die cast aluminium body with microprismatic diffuser



V410006

Light Data

Lumens per Watt	90-105lm/W
Light Source	LED
CRI	80
Distribution	120°

MGCLD Downlight

V410001- V410006

Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Cut out (mm)	Diameter mm	Height mm
V410001	12W	90	1080	3000K	90-100	110	80
V410002	12W	100	1210	4000K	90-100	110	80
V410003	24W	95	2380	3000K	160-180	190	100
V410004	24W	105	2510	4000K	160-180	190	100
V410005	34W	90	3200	3000K	200-220	230	110
V410006	34W	105	3630	4000K	200-220	230	110

Options

OPTION	CODE
1-10V Dimming	/D
DALI Dimming	/DL
DSI Digital Dimming	/DD
Leading/Trailing Edge Dimming	/TD
3 Hour Emergency	/M3
Self Test 3 Hour Emergency	/ST