

Corona 1

V417101- V417117

Description

The Corona 1 is a range of circular or square wall mounted bulkheads.

Environment

Outdoor/Indoor

Installation

Designed to be wall mounted

Application

For use apartment blocks, corridors, hotels, stairwells and other similar applications.




General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	3000K/4000K
LED Lifetime	50,000hrs
Operating temp	-15°C to 35°C
Materials	Polycarbonate base and diffuser

Light Data

Lumens per Watt	75-85lm/W
Light Source	LED
CRI	80
Distribution	110°



V417101

Corona 1

V417101- V417117

Product Variants

Product Code	Description	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Diameter mm	Height mm
V417101	Circular Black	12W	85	1040	3000K	300	100
V417102	Circular Black	12W	85	1040	4000K	300	100
V417103	Circular White	12W	85	1040	3000K	300	100
V417104	Circular White	12W	85	1040	4000K	300	100
V417105	Circular Black	18W	80	1460	3000K	350	120
V417106	Circular Black	18W	80	1460	4000K	350	120
V417107	Circular White	18W	80	1460	3000K	350	120
V417108	Circular White	18W	80	1460	4000K	350	120
V417109	Circular Black	24W	85	2085	3000K	400	120
V417110	Circular Black	24W	85	2085	4000K	400	120
V417111	Circular White	24W	85	2085	3000K	400	120
V417112	Circular White	24W	85	2085	4000K	400	120
V417113	Circular Black Eyelid	12W	75	950	4000K	350	120
V417114	Oval Black	10W	90	950	4000K	300	100
V417115	Oval White	10W	90	950	4000K	300	100

Product Code	Description	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Length & Width mm	Height mm
V417116	Square Black	12W	75	950	4000K	290	100
V417117	Square White	12W	75	950	4000K	290	100

Corona 1

V417101- V417117

Options

OPTION	CODE
1-10V Dimming	/D
DALI Dimming	/DL
DSI Digital Dimming	/DD
Leading/Trailing Edge Dimming	/TD
3 Hour Emergency	/M3
Self Test 3 Hour Emergency	/ST
Inbuilt Corridor Function	/CF
Inbuilt Microwave Sensor	/MS
Inbuilt Photocell	/PC
Night Light	/NL



V417113



V417114