

Description

The MGCYG is an architectural LED wall washer with symmetrical light distribution.

Environment

Outdoor/indoor

Installation

Designed to be surface mounted



Application

Suitable for indoor and outdoor accent lighting

5YR Warranty	 IP66 Protection	50,000hrs Lifetime	 IK09 Toughness
------------------------	---	------------------------------	--

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.95
Light Source	LED
LED Lifetime	50,000hrs/ L80B50
Operating temperature	-25°C to +40°C
Materials	Extruded aluminium body, light grey finish Tempered glass diffuser, impact resistant
Installation	Suitable for wall mounting

Light Data

Lumens per Watt	105-127lm/W
-Light Source	LED
CRI	80
Optics	30°

Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Length mm	Width mm	Height mm	Weight kg
MGCYG LED1X1900 D775 T740 L30	15.8	120	1897	4000	705	82	164	3
MGCYG LED1X2400 D776 T740 L30	22.6	105	2370	4000	705	82	164	3
MGCYG LED1X3200 D777 T740 L30	29.9	106	3162	4000	705	82	164	3
MGCYG LED1X3800 D778 T740 L30	29.9	127	3794	4000	1265	82	164	6
MGCYG LED1X4800 D779 T740 L30	42.7	111	4740	4000	1265	82	164	6
MGCYG LED1X6400 D780 T740 L30	59.7	106	6324	4000	1265	82	164	6

Options

Driver with DALI interface	DALI
Optics with 30x30° beam angle	LS30
3000K	T730
4000K	T740