

Description

The MGTUBS is an architectural LED wall mounted luminaire with up and down light distribution.

Environment

Outdoor

Installation

Designed to be surface mounted

Application

Suitable for outdoor facade lighting



General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.50
Light Source	LED
LED Lifetime	30,000hrs/ L70B50
Operating temperature	-25°C to +40°C
Materials	Die-cast aluminium body, dark grey finish Tempered glass diffuser, impact resistant
Installation	Suitable for wall mounting

Light Data

Lumens per Watt	70lm/W
Light Source	1xGU10/ 2xGU10 LED
CRI	80
Optics	30° 90°


Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Length mm	Width mm	Height mm	Weight kg
MGTUBS 2GU10 013					90	90	300	1.4
MGTUBS 1GU10 014 UP					90	90	158	1.3
MGTUBS 1GU10 015 DOWN					90	90	158	1.3
MGTUBS LED2X400 B194 T840 L90	10	70	700	4000	90	90	300	1.5
MGTUBS LED2X400 B194 T840 L30	10	70	700	4000	90	90	300	1.5
MGTUBS UP LED1X400 B195 T840 L90	5	70	350	4000	90	90	158	1.4
MGTUBS UP LED1X400 B195 T840 L30	5	70	350	4000	90	90	158	1.4


Options

With up light source only	UP
With down light source only	DOWN
LED bulb with 30° beam angle	L30
LED bulb with 90° beam angle	L90
RAL Colour	RAL
3000K	T830
4000K	T840

Photometrics



L30



L90