

MGN54 Downlight

V49101 -V49105

Description

The MGN54 is an IP54 recessed LED circular downlight, ideal for corridors, reception areas, retail and showrooms.

Environment

Indoor

Installation

Designed to recessed into ceiling

Application

For use in corridors, retail, showrooms and other similar applications.



5YR

Warranty



Protection

50,000hrs

Lifetime

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	3000K, 4000K or 6000K available
LED Lifetime	50,000hrs
Operating temp	0°C to 30°C
Materials	Die cast aluminium body with white finish

Light Data

Lumens per Watt	80-105lm/
Light Source	LED
CRI	80
Distribution	Direct

MGN54 Downlight

V49101 -V49105

Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Cut-out (mm)	Diameter mm	Height mm
V49101	18	80-105	1460/1850/1730	3CCT	160-170	190	45
V49102	25	90-100	2250/2750/2500	3CCT	200-210	228	45
V49103	35	75-90	2645/3186/2879	3CCT	200-210	228	45
V49104	45	>85	4000	3000K	230-260	280	52
V49105	45	>85	4200	4000K	230-260	280	52

Options

OPTION	CODE
1-10V Dimming	/D
DALI Dimming	/DL
DSI Digital Dimming	/DD
Leading/Trailing Edge Dimming	/TD
3 Hour Emergency	/M3
Self Test 3 Hour Emergency	/ST

