

MN3 Panel

V47601 - V47603

Description

The MN3 is a range of recessed direct lighting luminaires suitable for areas that require a higher light output.

Environment

Indoor

Installation

Designed to be fitted in standard 15mm or 24mm ceiling grid

Application

For use in commercial applications.



5YR Warranty	 IP20 Protection	50,000hrs Lifetime
------------------------	---	------------------------------

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	LED
CCT	4000K
LED Lifetime	50,000hrs
Operating temp	-15°C to 25°C
Materials	Steel body white finish, Opal cover
Installation	To fit in standard 15mm or 24mm ceiling grid

Light Data

Lumens per Watt	105lm/W
Light Source	LEDs
CRI	80
Distribution	110°

MN3 Panel

V47601 - V47603

Product Variants

Product Code	System Power (W)	Lumens (lm)	CCT (K)	Cut out mm	Length mm	Width mm	Height mm
V47601	30W	3250	4000	580x580	595	595	110
V47602	40W	4200	4000	580x580	595	595	110
V47603	50W	6300	4000	1180x580	1195	595	110

Options

OPTION	CODE
1-10V Dimming	/D
DALI Dimming	/DL
DSI Digital Dimming	/DD
Trailing Edge Dimming	/TD
3 Hour Emergency	/M3
3 Hour Emergency Self Test	/ST
CCT 3000K or 6000K	/3K or /6K